

Presented By: State Line Lighting LLC

Contact Phone: (704) 543-3133

Contact E-mail: sales@statelineighting.com

Customer Name:

Project Name:

Fixture Type:

GE
Lighting**10310 - GE Daylight Starcoat® T8****F30T8/D****Product Photo****GENERAL CHARACTERISTICS**

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	8 mg
Mercury-Picogram per mean lm hr	656.4
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Soda lime
Rated Life Hours-nominal	7500 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	1625 lm
Nominal Initial Lumen per Watt	62
Initial Lumens-nominal	1850 lm
Color Rendering Index-CRI	75
Color Temperature	6500 K

DIMENSIONS

Bulb Diameter (DIA) <Max>	1.1 in
Bulb Diameter (DIA) <Min>	0.94 in
Diameter	1.0 in
End of Base Pin to Pin	35.67 in
Face to End of Opposing Pin (B) <Max>	35.5 in
Face to End of Opposing Pin (B) <Min>	35.4 in
Nominal Length	36.0 in

ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX)	1.7
Cathode Resistance Ratio - Rh/Rc (MIN)	4.250
Cathode Resistance Ratio - Rh/Rc (MAX)	6.500
Rated power (Watts)	30 W

CAUTIONS & WARNINGS**Caution**

Lamp may shatter and cause injury if broken

Wear safety glasses and gloves when handling lamp.

Do not use excessive force when installing lamp.

Warning

Risk of Electric Shock

Turn power off before inspection

installation or removal.