





- Ompatible with Instant Start & Programmed Start ballasts
- Exceptional efficacy 124 LPW
- Suitable for use in totally enclosed fixtures
- Wide beam design: 280° light emitting area
- O-10V dimming















PRO











## **EFFICIENCY AT WORK**



## **SPECIFICATIONS**

Product	97745	97746	97747
Model	17PLL/830/DIR	17PLL/835/DIR	17PLL/840/DIR
Туре	PLL	PLL	PLL
Base	2G11	2G11	2G11
Power (W)	17	17	17
Voltage - Frequency	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz
Color Temp. (ANSI)	Warm White 3000K	Neutral White 3500K	Cool White 4000K
CRI (Ra)	80	80	80
Typical lumens (lm)	2000	2050	2100
Efficacy (LPW)	118	121	124
Light Emitting Area	280°	280°	280°
Beam Angle	120°	120°	120°
Dimmable	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9
THD	<20%	<20%	<20%
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000
Dia. x MOL	1.71"x22.48" (44x571mm)	1.71''x22.48'' (44x571mm)	1.71''x22.48'' (44x571mm)
Weight (lb. / g)	0.31lb. / 140g	0.31lb. / 140g	0.31lb. / 140g

## BALLAST PERFORMANCE

		3000K	3500K	4000K
Bare Lamp (W)	System (W)	Lumens	Lumens	Lumens
17	21	2000	2050	2100

<sup>\*</sup> Suitable for use in totally enclosed fixtures

<sup>\*\*</sup> Suitable for damp locations. Not for use where directly exposed to the weather or water