G25 6W DIM. TITANIUM LED SERIES









- Perfect for decorative retrofit needs
- Omnidirectional: 275° beam angle
- U High efficacy 75 LPW in Warm White
- Powerful 450 lumens in 2700K
- Comfortable warm diffused light
- Instant ON and compatible with motion sensors




















40W Inc.

80% Energy Savings

\$110 Savings per lamp*















TRADITIONAL INCANDESCENT LIGHTING EFFECT



G25 6W DIM. TITANIUM LED SERIES









SPECIFICATIONS

Product Model 97729 Model 6G25DIM/827 Type G25 Base E26 Power (W) 6 Voltage - Frequency 120V 60Hz Color Temp. (ANSI) Warm White 2700K CRI (Ra) (typ.) 80 Typical lumens (Im) 450 Efficacy (LPW) 75 Beam Angle 275° Dimmable Yes** Power Factor 0.9 Rated Lifetime - L70 (hrs.) 25,000		
Base E26 Power (W) 6 Voltage - Frequency 120V 60Hz Color Temp. (ANSI) Warm White 2700K CRI (Ra) (typ.) 80 Typical lumens (Im) 450 Efficacy (LPW) 75 Beam Angle 275° Dimmable Yes** Power Factor 0.9		
Power (W) 6 Voltage - Frequency 120V 60Hz Color Temp. (ANSI) Warm White 2700K CRI (Ra) (typ.) 80 Typical lumens (Im) 450 Efficacy (LPW) 75 Beam Angle 275° Dimmable Yes** Power Factor 0.9	Туре	G25
Voltage - Frequency 120V 60Hz Color Temp. (ANSI) Warm White 2700K CRI (Ra) (typ.) 80 Typical lumens (Im) 450 Efficacy (LPW) 75 Beam Angle 275° Dimmable Yes** Power Factor 0.9	Base	E26
Color Temp. (ANSI) CRI (Ra) (typ.) 80 Typical lumens (Im) Efficacy (LPW) 75 Beam Angle Dimmable Yes** Power Factor Warm White 2700K 80 Yes**	Power (W)	6
CRI (Ra) (typ.) Typical lumens (Im) Efficacy (LPW) Beam Angle Dimmable Power Factor 80 75 80 75 80 75 80 75 80 75 80 90 90 90 90 90 90 90 90 90	Voltage - Frequency	120V 60Hz
Typical lumens (Im) Efficacy (LPW) Beam Angle Dimmable Yes** Power Factor 0.9	Color Temp. (ANSI)	Warm White 2700K
Efficacy (LPW) 75 Beam Angle 275° Dimmable Yes** Power Factor 0.9	CRI (Ra) (typ.)	80
Beam Angle 275° Dimmable Yes** Power Factor 0.9	Typical lumens (Im)	450
Dimmable Yes** Power Factor 0.9	Efficacy (LPW)	75
Power Factor 0.9	Beam Angle	275°
	Dimmable	Yes**
Rated Lifetime - L70 (hrs.) 25,000	Power Factor	0.9
	Rated Lifetime - L70 (hrs.)	25,000
Dia. x MOL 3.15"x4.76" (80x121mm)	Dia. x MOL	3.15"x4.76" (80x121mm)
Weight (lb. / g) 0.14lb. / 64g	Weight (lb. / g)	0.14lb. / 64g

 $^{^{\}star}$ Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$2 incandescent with 1000-hr lifetime, \$16 LED with 25,000-hr lifetime

^{**} List of tested dimmer switches available on website

*** Not intended for use in totally enclosed fixtures

**** Suitable for damp locations. Not for use where directly exposed to weather or water