

A19 9W DIM. TITANIUM LED SERIES 4.0



PRO



9W REPLACES




60W Inc.

80% Energy Savings

\$151 Savings per lamp*


- ⌚ Omnidirectional: 300° beam angle
- ⌚ Exceptional efficacy 89 LPW in Warm White
- ⌚ 40% more energy savings than CFL
- ⌚ Comfortable warm diffused light
- ⌚ Natural A-lamp shape fits all applications
- ⌚ Ideal for lamps with shades



A19 PRODUCT FEATURES

Omnidirectional Lighting

This A19 meets the new ENERGY STAR V1.1 requirements for omnidirectional bulbs by providing 300° of evenly distributed light intensity. In the 135° to 180° zone, this lamp emits 65% more lumens than what is required by ENERGY STAR, providing a fuller light than other LED A-lamps.



Exceptional Efficacy



At 89 LPW, this lamp's efficacy is more than 10% higher than the Tier 1 LED A19 60W replacement industry average and exceeds new ENERGY STAR requirements by upwards of 62%. This energy-saving performance makes this lamp a smart retrofit choice for incandescent and CFL bulbs.

A19 9W DIM. TITANIUM LED SERIES 4.0

APPLICATIONS

General Lighting



Downlighting



Uplighting



Ref.#: DSC031-A19-9W

SPECIFICATIONS

| Product Model | 40741 9A19G4DIM/824 | 40742 9A19G4DIM/827 | 40743 9A19G4DIM/830 | 40744 9A19G4DIM/840 |
|------------------------------------|------------------------|------------------------|------------------------|------------------------|
| Type | A19 | A19 | A19 | A19 |
| Base | E26 | E26 | E26 | E26 |
| Power (W) | 9 | 9 | 9 | 9 |
| Voltage - Frequency | 120V 60Hz | 120V 60Hz | 120V 60Hz | 120V 60Hz |
| Color Temp. (ANSI) | Extra Warm White 2400K | Warm White 2700K | Warm White 3000K | Natural White 4000K |
| CRI (Ra) (typ.) | 80 | 80 | 80 | 80 |
| Typical lumens (lm) | 700 | 800 | 800 | 850 |
| Efficacy (LPW) | 78 | 89 | 89 | 94 |
| Beam Angle | 300° | 300° | 300° | 300° |
| Dimmable | Yes** | Yes** | Yes** | Yes** |
| Power Factor | 0.9 | 0.9 | 0.9 | 0.9 |
| Rated Lifetime - L70 (hrs.) | 25,000 | 25,000 | 25,000 | 25,000 |
| Dia. x MOL | 2.36"x4.57" (60x116mm) | 2.36"x4.57" (60x116mm) | 2.36"x4.57" (60x116mm) | 2.36"x4.57" (60x116mm) |
| Weight (lb. / g) | 0.26lb. / 118g | 0.26lb. / 118g | 0.26lb. / 118g | 0.26lb. / 118g |

* Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$2 incandescent with 1000-hr lifetime, \$16 LED with 25,000-hr lifetime

** List of tested dimmer switches available on website

*** Not intended for use in enclosed fixtures

**** Suitable for damp locations. Not for use where directly exposed to weather or water