



Cat# 71564A

220 Watts
Slipfitter Mount

Dimming:
PWM/TIME/0-5V/0-10V



QPL ID #
PLTHR8UMTKIA

Model : 71564		
OVERALL LAMP PARAMETERS	Input Voltage	100-277VAC 50/60HZ
	Input Current	1.82A Max
	Input Power	220W
	Power Factor	PF≥ 0.9
	Luminance	27600 LM
	Luminous Efficiency	125 LM/W
	CRI	>80
	Beam Angle	Type III 150 x 105°
LED DRIVER	Main Structure	Aluminium + PC Lens
	Output Voltage	36-60VDC
	Output Current	5.3A
	Driver Efficiency	88%
LED	LED Manufacturer	Philips
	LED Type	3030 LED
	LED Quantity	120 PCS
	LED Efficacy	150 LM/W
Photocell	Color Temperature	5000K
	-	Not Included
LIFESPAN & ENVIRONMENT	Lifespan	50,000+ Hrs.
	Warranty	5 Years
	IP Rating	IP65 Wet Locations
	Operating Temperature	-40F - +131F
SAFETY&EMC	Storage Temperature.Humidity	-40°C—+80°C , 10—90% RH
	Safety Norms	UL 1598,UL8750, EN60598, EN61347-2-13, EN62031, EN62471
	Withstand Voltage	I/P-FG: 2121VDC
	Grounding Resistance	≤0.5Ω,OK
OTHERS	Electromagnetic Compatibility	EN55015, EN61000-2-3, EN61000-3-3, EN61547
	Dimension	Pls refer to attached dimension drawing
	Net Weight	KG
	Gross Weight	KG
	Packing Size	master carton: L*W*Hmm
	Q'ty / Carton	1PCS
	Volume	
	EPA Rating	1.68ft²

Dimension :

