



Dimming:
PWM/TIME/0-5V/0-10V

Cat# 71575A
150 Watts
Pole Mount



QPL ID #
PLMWEKHWJOBH

Model: 71575A		
OVERALL LAMP PARAMETERS	Input Voltage	100-277VAC 50/60HZ
	Input Current	1.299A Max
	Input Power	150W
	Power Factor	PF≥ 0.90
	Luminance	18300 LM
	Luminous Efficiency	125 LM/W
	CRI	>80
	Beam Angle	Type III 150 x 105°
Main Structure	Aluminium + PC Lens	
LED DRIVER	Output Voltage	36-60VDC
	Output Current	4.4A
	Driver Efficiency	88%
LED	LED Manufacturer	Philips
	LED Type	3030 LED
	LED Quantity	120 PCS
	LED Efficacy	150 LM/W
Color Temperature	5000K	
Photocell	-	Not Included
LIFESPAN & ENVIRONMENT	Lifespan	50000+ Hrs.
	Warranty	5 Years
	IP Rating	IP65 Wet Locations
	Operating Temperature	-40F - +131F
Storage Temperature, Humidity	-40°C—+80°C , 10—90% RH	
SAFETY&EMC	Safety Norms	UL1598, UL8750, EN60598, EN61347-2-13, EN62031, EN62471
	Withstand Voltage	I/P-FG: 2121VDC
	Grounding Resistance	≤0.5 Ω, OK
	Electromagnetic Compatibility	EN55015, EN61000-2-3, EN61000-3-3, EN61547
OTHERS	Dimension	Pls refer to attached dimension drawing
	Q'ty / Carton	1PCS
	Volume	
	EPA Rating	1.16ft²

Dimensions:

